

C4: COMBINED IOs

Our powerful controller for almost any IoT, Building Automation or Industrial Automation task. Based on the Raspberry Pi® Compute Module 4 with 2/4/8GB build in RAM, 32 GB SD CARD and stable 12-48Vdc power supply, 1xEthernet, 2xUSB 2.0, 1xMini-HDMI. LINUX is preinstalled. Additional versions with preinstalled CODESYS® runtime or Node Red, OpenHAB,... available.

RESI-C4-A-64DI60DO4AIOX-xGB	Raspberry Pi CM4®	XT12 213x110x62mm	64xDI	64 Digital Inputs	LOGIC INPUT 12...48V= ≤1.8mA
			60xDO	60 Digital Outputs	DIGITAL OUTPUT ≤30V= ≤700mA Output is shortcut & over heat protected. Organized in 4 group with 15 outputs each. Each output group is externally supplied. Max. 1.8A power supply for output group.
			4xAIOX Universal analog Inputs or outputs	4 Universal Inputs or Outputs Each channel can be configured to: Analog Input or Analog Output or RTD Sensor Input or Digital Input	ANALOG INPUTS 0...10V or 0..20mA or 4..20mA ±0.2% 16 Bit ANALOG OUTPUTS 0...10V or 0..20mA or 4..20mA ±0.3% 13 Bit RTD Sensors 0...80Ω 0.5%±0.5 16 Bit 80...200Ω 0.3% 16 Bit 200...10kΩ 0.2% 16 Bit 10kΩ...20kΩ 0.3% 16 Bit 20kΩ...100kΩ 0.8% 16 Bit 100kΩ...200kΩ 1.0% 16 Bit 200kΩ...1MΩ 8.0% 16 Bit LOGIC INPUT ≤40V ≤1.8mA DRY CONTACT 0.5...24.5mA
RESI-C4-A-64DI60DO8AIOX-xGB	Raspberry Pi CM4®	XT12 213x110x62mm	8xAIOX Universal analog Inputs or outputs	Rest like RESI-C4-A-64DI60DO4AIOX-xGB	
RESI-C4-A-64DI60DO16AIOX-xGB	Raspberry Pi CM4®	XT12 213x110x62mm	16xAIOX Universal analog Inputs or outputs	Rest like RESI-C4-A-64DI60DO4AIOX-xGB	