

RESI-DALI-xxx

Our powerful master gateways between DALI light bus and host. Host protocols: MODBUS/RTU, MODBUS/TCP or ASCII text. Communicate with DALI 1.0 ballasts or with DALI 2.0 control gears. Support of DALI device type DT8 for RGB and RGBW LED stripes. Use our RESI-DALI-PS as power supply for your DALI light system. Or use our all-in-one solution RESI-DALI+PS-SIO or RESI-DALI+PS-ETH to communicate with your DALI bus system with only one unit.



RESI-DALI-SIO	DALI Master	RS232 RS485	NO integrated DALI power supply	DALI 1.0 DALI 2.0	64 Ballasts	MODBUS/RTU Slave ASCII text protocol
RESI-DALI-ETH	DALI Master	ETHERNET	NO integrated DALI power supply	DALI 1.0 DALI 2.0	64 Ballasts	MODBUS/TCP Server ASCII text socket
RESI-DALI-PS	DALI Power supply	12-48V= Power supply	DALI output current $\leq 200\text{mA}$			



RESI-DALI+PS-SIO	DALI Master with integrated DALI power supply	RS485	Switchable DALI power supply $\leq 250\text{mA}$	DALI 1.0 DALI 2.0	64 Ballasts	MODBUS/RTU Slave ASCII text protocol
RESI-DALI+PS-ETH	DALI Master with integrated DALI power supply	ETHERNET	Switchable DALI power supply $\leq 250\text{mA}$	DALI 1.0 DALI 2.0	64 Ballasts	MODBUS/TCP Server ASCII text socket