

RESI-DMX-SIO

Our powerful master gateway between DMX light bus and host. Host protocols: MODBUS/RTU or ASCII text. Host communication via RS232 or RS485 serial interface. DMX master communication with DMX lamps in one DMX universe. Adjustable time between two DMX frames. Configuration & test of DMX light system with our free software MODBUSConfigurator.



<p>HOST MODBUS/RTU MASTER ASCII TEXT</p> <p>RS232 RS485</p> <p>RESI</p> <p>DMX</p> <p>DMX LIGHT NETWORK</p> <p>■ ■ ■</p>	<p>DMX pause Adjustable DMX pause between 2 DMX frames</p>	<p>DMX frame Configurable DMX frame length</p>	<p>DMX Support of 512 DMX register</p>	<p>DMX512 unidirectional master protocol</p>
	<p>Functionality MODBUS to DMX master to control a DMX light system in one DMX universe with max. 512 DMX register. Unidirectional DMX master with adjustable DMX frame repeat time.</p>		<p>Serial Interface RS232 or RS485 300..256000 baud No, even, odd parity 8 data bits 1 or 2 stop bits</p>	<p>1xRS232 MODBUS/RTU slave ASCII text protocol</p> <p>1xRS485 MODBUS/RTU slave ASCII text protocol</p>
	<p>MODBUSConfigurator free configuration software</p>	<p>DIN EN 50022 Snap-on for DIN-Rail</p>	<p>CEM17 17.5x90x56.4mm</p>	<p>12-48V= Power supply</p>