

RESI-KNX-SIO

Our powerful master gateway between KNX bus and host. Host protocols: MODBUS/RTU or ASCII text. Host communication via RS232 or RS485 serial interface. Bidirectional communication with KNX devices. Support of all KNX group addresses. Mapping & testing between KNX bus and MODBUS registers with our free software MODBUSConfigurator.



<p>HOST MODBUS/RTU MASTER ASCII TEXT</p> <p>RS232 RS485</p> <p>RESI</p> <p>KNX</p> <p>KNX NETWORK</p>	<p>KNX↔MODBUS bidirectional gateway</p>	<p>KNX 65.536 group addresses supported</p>	<p>MODBUS all common data types supported</p>	<p>external KNX power supply necessary</p>
	<p>Functionality Bidirectional gateway between MODBUS holding registers and KNX group addresses with automatic data type conversion. Simple configuration of mapping between KNX groups and MODBUS registers. Easy test of mapping.</p>	<p>Serial Interface RS232 or RS485 300..256000 baud No, even, odd parity 8 data bits 1 or 2 stop bits</p>	<p>1xRS232 MODBUS/RTU slave ASCII text protocol</p>	<p>1xRS485 MODBUS/RTU slave ASCII text protocol</p>
	<p>MODBUSConfigurator free configuration software</p>	<p>DIN EN 50022 Snap-on for DIN-Rail</p>	<p>CEM17 17.5x90x56.4mm</p>	<p>12-48V= Power supply</p>