

RESI-ENO-xxx

Our powerful master gateways between ENOCEAN sensors and host. Host protocols: MODBUS/RTU, MODBUS/TCP or ASCII text. Special versions with ENOCEAN ESP3 protocol. Read-out of ENOCEAN sensors. Support of all ENOCEAN frames. Additional Antennas for better radio signal.



RESI-ENO-SIO	ENOCEAN Gateway	RS232 RS485	ENOCEAN	EU 868MHz	MODBUS/RTU Slave ASCII text protocol
RESI-ENO-ETH	ENOCEAN Gateway	ETHERNET	ENOCEAN	EU 868MHz	MODBUS/TCP Server ASCII text socket
RESI-ENOCEAN-ANT	ENOCEAN Antenna	116mm rotation 360°, tilt 90° SMA	ENOCEAN	EU 868MHz	
RESI-ENOCEAN-ANT2	ENOCEAN Antenna with magnetic base	295mm cable 4m, magnetic base Ø 50mm, SMA	ENOCEAN	EU 868MHz	



RESI-ENO-GW	ENOCEAN Gateway	RS232 RS485	ENOCEAN	EU 868MHz	ESP3® protocol
RESI-ENOGW-ETH	ENOCEAN Gateway	ETHERNET	ENOCEAN	EU 868MHz	ESP3® protocol