



# RESI-ENO-ETH

Our powerful master gateway between ENOCEAN sensors and host. Host protocols: MODBUS/TCP or ASCII text socket. Host communication via Ethernet interface. Bidirectional communication with ENOCEAN devices. Support of all ENOCEAN protocol types. ENOCEAN Antenna connector: SMA, Mapping & testing between ENOCEAN sensors and MODBUS registers with our free software MODBUSConfigurator.



<p><b>HOST</b> MODBUS/TCP CLIENT ASCII TEXT SOCKET</p> <p>ETHERNET</p>  <p>ENOCEAN 868MHz</p> 	<p><b>ENOCEAN↔ MODBUS</b> bidirectional gateway</p>	<p><b>ENOCEAN</b> All frame types supported</p>	<p><b>MODBUS</b> all common data types supported</p>	<p><b>868MHz</b> EU Version</p>
	<p><b>Functionality</b> Bidirectional gateway between MODBUS holding registers and ENOCEAN sensors with automatic data type conversion. Simple configuration of mapping between ENOCEAN sensors and MODBUS registers. Easy testing of mapping.</p>		<p><b>Ethernet</b> Web Server for IP V4 setup MODBUS/TCP or MODBUS/RTU via Ethernet or ASCII text protocol</p>	<p><b>1xETHERNET</b> 10/100MBit RJ45</p>
	<p><b>MODBUSConfigurator</b> free configuration software</p>	<p><b>DIN EN 50022</b> Snap-on for DIN-Rail</p>	<p><b>CEM35</b> 35.8x90x56.4mm</p>	<p><b>IP settings</b> DHCP or static IPV4 settings</p>
				<p><b>12-48V=</b> Power supply</p>