

SLIMIOs:SOLID STATE

Our powerful IO modules in a very slim housing with MODBUS/RTU or MODBUS/TCP host interface or ASCII text protocol. Control and monitor all integrated IOs via MODBUS registers or via simple ASCII text strings. Integrated WATCHDOG function sets all outputs to predefined states in case of a communication breakdown.

RESI-2SSR-1A-SIO	RS232 RS485	CEM17 17.5x90x56.4mm	2xSSR 1A	2 Solid State Outputs	SOLID STATE RELAY OUTPUT $\leq 230V=\sim$ $\leq 1A$ 2xForm A
RESI-2SSR-1A-ETH	ETHERNET	CEM35 35.8x90x56.4mm			
RESI-2SSR-3A-SIO	RS232 RS485	CEM17 17.5x90x56.4mm	2xSSR 3A	2 Solid State Outputs	SOLID STATE RELAY OUTPUT $\leq 60V=\sim$ $\leq 3A$ 2xForm A
RESI-2SSR-3A-ETH	ETHERNET	CEM35 35.8x90x56.4mm			
RESI-2SSR-6A-SIO	RS232 RS485	CEM17 17.5x90x56.4mm	2xSSR 6A	2 Solid State Outputs	SOLID STATE RELAY OUTPUT $\leq 60V=\sim$ $\leq 6A$ 2xForm A
RESI-2SSR-6A-ETH	ETHERNET	CEM35 35.8x90x56.4mm			