

BIGIOs:SOLID STATE & DI

Our powerful IO modules in a very slim housing with MODBUS/RTU or MODBUS/TCP host interface or ASCII text protocol. Control and monitor all integrated IOs via MODBUS registers or via simple ASCII text strings. Integrated WATCHDOG function sets all outputs to predefined states in case of a communication breakdown.

| | | | | | |
|---------------------|----------|---------------------|-------------|--------------------------|--|
| RESI-7RI5SSR-1A-SIO | RS485 | XT8 143x110x62mm | 7xRI | 7 Digital Inputs | LOGIC INPUT 12...250V~= ≤1.8mA Each input has its own 2pin plug-in terminal |
| RESI-7RI5SSR-1A-ETH | ETHERNET | XT8 143x110x62mm | | | |
| | | | 5xSSR 1A | 5 Solid State Outputs | SOLID STATE RELAY OUTPUT ≤230V=~ ≤1A 5xForm A |
| RESI-7RI5SSR-3A-SIO | RS485 | XT8 143x110x62mm | 7xRI | 7 Digital Inputs | LOGIC INPUT 12...250V~= ≤1.8mA Each input has its own 2pin plug-in terminal |
| RESI-7RI5SSR-3A-ETH | ETHERNET | XT8 143x110x62mm | | | |
| | | | 5xSSR 3A | 5 Solid State Outputs | SOLID STATE RELAY OUTPUT ≤60V=~ ≤3A 5xForm A |
| RESI-7RI5SSR-6A-SIO | RS485 | XT8 143x110x62mm | 7xRI | 7 Digital Inputs | LOGIC INPUT 12...250V~= ≤1.8mA Each input has its own 2pin plug-in terminal |
| RESI-7RI5SSR-6A-ETH | ETHERNET | XT8 143x110x62mm | | | |
| | | | 5xSSR 6A | 5 Solid State Outputs | SOLID STATE RELAY OUTPUT ≤60V=~ ≤6A 5xForm A |