

# BIGIOs: DIGITAL OUT

Our powerful IO modules in a very slim housing with MODBUS/RTU or MODBUS/TCP host interface or ASCII text protocol. Control and monitor all integrated IOs via MODBUS registers or via simple ASCII text strings. Integrated WATCHDOG function sets all outputs to predefined states in case of a communication breakdown.

RESI-6DO-SIO	RS485	XT4 213x110x62mm	6xDO	6 Digital Outputs	DIGITAL OUTPUT $\leq 30V=$ $\leq 700mA$  Output is shortcut & over heat protected. Organized in 2 groups with 6 outputs each. Each output group is externally supplied. Max. 1.8A power supply for output group.
RESI-6DO-ETH	ETHERNET	XT4 213x110x62mm			
RESI-12DO-SIO	RS485	XT4 213x110x62mm	12xDO	12 Digital Outputs	DIGITAL OUTPUT $\leq 30V=$ $\leq 700mA$  Output is shortcut & over heat protected. Organized in 2 groups with 6 outputs each. Each output group is externally supplied. Max. 1.8A power supply for output group.
RESI-12DO-ETH	ETHERNET	XT4 213x110x62mm			
RESI-24DO-SIO	RS485	XT4 213x110x62mm	24xDO	24 Digital Outputs	DIGITAL OUTPUT $\leq 30V=$ $\leq 700mA$  Output is shortcut & over heat protected. Organized in 2 groups with 12 outputs each. Each output group is externally supplied. Max. 1.8A power supply for output group.
RESI-24DO-ETH	ETHERNET	XT4 213x110x62mm			
RESI-30DO-SIO	RS485	XT8 143x110x62mm	30xDO	30 Digital Outputs	DIGITAL OUTPUT $\leq 30V=$ $\leq 700mA$  Output is shortcut & over heat protected. Organized in 2 groups with 15 outputs each. Each output group is externally supplied. Max. 1.8A power supply for output group.
RESI-30DO-ETH	ETHERNET	XT8 143x110x62mm			
RESI-60DO-SIO	RS485	XT12 213x110x62mm	60xDO	60 Digital Outputs	DIGITAL OUTPUT $\leq 30V=$ $\leq 700mA$  Output is shortcut & over heat protected. Organized in 4 groups with 15 outputs each. Each output group is externally supplied. Max. 1.8A power supply for output group.
RESI-60DO-ETH	ETHERNET	XT12 213x110x62mm			
RESI-90DO-SIO	RS485	XT12 213x110x62mm	90xDO	90 Digital Outputs	DIGITAL OUTPUT $\leq 30V=$ $\leq 700mA$  Output is shortcut & over heat protected. Organized in 6 groups with 15 outputs each. Each output group is externally supplied. Max. 1.8A power supply for output group.
RESI-90DO-ETH	ETHERNET	XT12 213x110x62mm			