

BIGIOs: ANALOG IOs

Our powerful IO modules in a very slim housing with MODBUS/RTU or MODBUS/TCP host interface or ASCII text protocol. Control and monitor all integrated IOs via MODBUS registers or via simple ASCII text strings. Integrated WATCHDOG function sets all outputs to predefined states in case of a communication breakdown.

RESI-12AIU-SIO	RS485	XT8 143x110x62mm	12xAIU	12 Analog Inputs	0...10V -10V...+10V	±0.1% 16 Bit
RESI-12AIU-ETH	ETHERNET	XT8 143x110x62mm				
RESI-12AOU-SIO	RS485	XT8 143x110x62mm	12xAOU	12 Analog Outputs	-10V...+10V	±0.1% 12 Bit
RESI-12AOU-ETH	ETHERNET	XT8 143x110x62mm				
RESI-8RTD-SIO	RS485	XT8 143x110x62mm	8xRTD	8 RTD Sensor Inputs	SENSORS: ±0.1% 24 Bit PT100 PT200 PT500 PT1000 NI120 NI1000-DIN43760 Ohm	
RESI-8RTD-ETH	ETHERNET	XT8 143x110x62mm		2-wire, 3-wire and 4-wire		
RESI-8RTD2-SIO	RS485	XT8 143x110x62mm	8xRTD	8 RTD Sensor Inputs	SENSORS: ±0.1% 24 Bit PT100 PT200 PT500 PT1000 NI120 NI1000-DIN43760 Ohm	
RESI-8RTD2-ETH	ETHERNET	XT8 143x110x62mm		2-wire		